

## SPECIFICATION FOR GAS OIL L-0,2-62

Turkmenbashi origin



No.	COMPONENT	FACT
1	50% of distillation, at temperature B Grad C, not more	275
2	96% of distillation, at temperature (end of distillation) grad C, not more	347
3	Flash point Dgr C	68
4	Kinematics viscosity at 20Dgr C	5,037
5	Octane number	49
6	Pour point Dgr C	-10
7	Mercaptan Sulphure	0.0028
8	Acidity for mg KON/100 cub cm	5.0
9	Iodine number in 100g/cub cm	5.6
10	Ash %, not more	0.0042
11	Total Sulphure %	0.12
12	Test on copper strip	Passed
13	Resins for 100 cub cm	22
14	Cloud point Dgr C	-5
15	Density at 20 C	831
16	Water sediments	NIL
17	Filterability coefficient	3
18	Coxing in % wt	0.08
19	H2S	NIL
20	Sediments	NIL

#564, 23<sup>rd</sup> Alley, Emergency Street,  
Bakhtiari Area, Erbil, Iraq  
Tel : (+96) 47509324793  
(+96) 47718552629

E-Mail: [info@mirolco.com](mailto:info@mirolco.com)

Website: [www.mirolco.com](http://www.mirolco.com)